







REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

✓	Poles	A±0.30	B±0.20
	02	7.0	3.5
	03	10.5	7.0
	04	14.0	10.5
	05	17.5	14.0
	06	21.0	17.5
⇩	Poles	A±0.35	B±0.25
	07	24.5	21.0
	08	28.0	24.5
	09	31.5	28.0
	10	35.0	31.5
	11	38.5	35.0
	12	42.0	38.5
⇩	Poles	A±0.40	B±0.30
	13	45.5	42.0
	14	49.0	45.5
	15	52.5	49.0
	16	56.0	52.5

	17	59.5	56.0
	18	63.0	59.5
⇩	Poles	A±0.45	B±0.35
	19	66.5	63.0
	20	70.0	66.5
	21	73.5	70.0
	22	77.0	73.5
	23	80.5	77.0
	24	84.0	80.5
⇩	Poles	A±0.50	B±0.40
	25	87.5	84.0
	26	91.0	87.5

Screws Torque: 1 In-Lb
Wire Range: 12~28 AWG
Rated: 20 Amperes.AC300V
Operation Temperature: -40°C~+105°C
Insulation withstands volt: AC1600V min
Insulation resistance: >2000MΩ DC500V

Part Number:

HD-352-XXP

02~26 Poles

	Material		Plating/Finish	Remark
A	Insulating body	PA66 UL 94V-0		Green
B	Terminal	Brass	Tin	
C	Screw	Steel	Yellow Zinc	
D	Cage Clamp	Brass	Tin	
E				

1 Size update From 7.60 to 7.50 (2018/10/17)

HOW DER
ELECTRONIC CO.,LTD

PART NAME	UNIT	REVISION
Teminal Blocks	MM	
CERTIFIED		SHEET 1/1

DESIGN	CHECK	APPROVED	DRAWING NO.
DATE 2009/09/03	DATE	DATE	

http://www.howder-tw.com
E-mail:info@howder-tw.com
Tel:886-2-2223-1026
Fax:886-2-2221-6471