

✓ Poles	A±0.30	B±0.20	17	131.14	121.92
02	16.94	7.62	18	138.86	129.54
03	24.56	15.24	↓ Poles	A±0.45	B±0.35
04	32.18	22.86	19	146.48	137.16
05	39.80	30.48	20	154.10	144.78
06	47.42	38.10	21	161.72	152.40
↓ Poles	A±0.35	B±0.25	22	169.34	160.02
07	55.04	45.72	23	176.96	167.64
08	62.66	53.34	24	184.58	175.26
09	70.28	60.96	↓ Poles	A±0.50	B±0.40
10	77.90	68.58	25	192.20	182.88
11	85.52	76.20	26	199.82	190.50
12	93.14	83.82	27	207.44	198.12
↓ Poles	A±0.40	B±0.30	28	215.06	205.74
13	100.76	91.44	29	222.68	213.36
14	108.38	99.06	30	230.30	220.98
15	116.00	106.68	31	237.92	228.60
16	114.30	114.30	32	236.22	236.22

Screws Torque: 12 In-Lb

Wire Range: 16~22 AWG

Rated: 15 Amperes, AC300V

Operation Temperature: -55°C~+105°C

Insulation withstands volt: AC2000V min

Insulation resistance: >1000MΩ DC500V

Part
Number:
FTB-704-XXP

02~32 Poles

Material	Plating/Finish	Remark
A Insulating body PA66 94V-0		Black
B Terminals	Brass	Tin
C Screws	Steel	Nickel
D Cover	PC	
E		



HOW DER
ELECTRONIC CO.,LTD

PART NAME
Terminal Blocks

UNIT
MM

REVISION

DESIGN	CHECK	APPROVED	DRAWING NO.
DATE	DATE	DATE	
2009/09/03			

