HOW DER

DATE 2009/08/26

SPECIFICATIONS

① Housing Material: Phenolic , Black
② Screw: M3.0 Nickel Plated Steel
③ Terminals: Tin Plated Brass

Screws Torque: 7 In-Lb
Wire Range: 14~22 WG
Rated: 10 Amperes.AC250V
Operation Temperature: -55°C~+150°C
Insulation withstands volt: AC2000V min
Insulation resistance: >1000MΩ or more at DC500V







Part Number:

FTB-10-O-□PH

Pole Size 2~24P

Tolerance ± 0.50

POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15
A	38	48	58	68	78	88	98	108	118	128	138	148	158	168
B	30	40	50	60	70	80	90	100	110	120	130	140	150	160

POLE	16	17	18	19	20	21	22	23	24
A	178	188	198	208	218	228	238	248	258
B	170	180	190	200	210	220	230	240	250

文件發行
2009.8.26
林姿伶

ROHS

CO/Name	HOW DER ELECTRIC CO.,LTD	REV.	CONTENT	DATE	NO.	PART NO.	DrawingNo		DATE		DrawingNo	FTB-1012
P/Name	Barrier type terminal block	△1			①							
					②		APPROVED		DATE		Scale	2:1(:)
					③						Sheet	1/1
http://www.howder-tw.com Tel:02-2223-1026					④		CHECK		DATE		Unit	mm
E-mail:howder.tb@msa.hinet.net Fax:02-2221-6471												