HOW DER

DATE 2009/08/25

SPECIFICATIONS

① Housing Material: PA 66(UL94V-0), Black
② Screw: M3.5 Nickel Plated Steel
③ Terminals: Tin Plated Brass
④ Cover: PC Transparent
Screws Torque: 15.7 In-Lb
Wire Range: 12~22 AWG
Rated: 20 Amperes.AC 250V(TUV)
25 Amperes.AC 300V(UL)
Operation Temperature: -55°C~+105°C
Insulation withstands volt: AC2000V min
Insulation resistance: >1000MΩ or more at DC500V

Part Number:

HD-121-□PH-□
C: With Cover
Pole Size 2~25P







POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15
A	39.4	48.9	58.4	67.9	77.4	86.9	96.4	105.9	115.4	124.9	134.4	143.9	153.4	162.9
B	28.5	38	47.5	57	66.5	76	85.5	95	104.5	114	123.5	133	142.5	152

POLE	16	17	18	19	20	21	22	23	24	25
A	172.4	181.9	191.4	200.9	210.4	219.9	229.4	238.9	248.4	257.9
B	161.5	171	180.5	190	199.5	209	218.5	228	237.5	247

文件發行
2019.07.25
黃琦婷

TÜV

ROHS

CO/Name	HOW DER ELECTRONIC CO.,LTD	REV.	CONTENT	DATE	POLES	A	B	DrawingNo		DATE		DrawingNo	HD-12095004
		⚠1	Size update From 18.0 to 17.8	2019 0528	02P~06P	±0.20	±0.15						
P/Name	Barrier type terminal block	⚠2	Size update From 0.8 to 0.9	2019 0702	07P~12P	±0.25	±0.20	APPROVED		DATE		Scale	2:1(:)
					13P~18P	±0.30	±0.25					Sheet	1/1
http://www.howder-tw.com	Tel:02-2223-1026				19P~24P	±0.40	±0.35	CHECK		DATE		Unit	mm
E-mail:info@howder-tw.com	Fax:02-2221-6471				25P~30P	±0.50	±0.40						