

✓	Poles	A±0.30	B±0.20
02		15.60	10.0
03		25.60	20.0
04		35.60	30.0
05		45.60	40.0
06		55.60	50.0
↓	Poles	A±0.35	B±0.25
07		65.60	60.0
08		75.60	70.0
09		85.60	80.0
10		95.60	90.0
11		105.60	100.0
12		115.60	110.0

Screws Torque: 3.5 In-Lb
Wire Range: 16~22 AWG
Rated: 10 Amperes,AC250V
Operation Temperature: -55°C~+100°C
Insulation withstands volt: AC2000V min
Insulation resistance: >1000MΩ/DC500V min
Part Number:

TS-502-10-XXP

02~12 Poles

Size update From 0.85 to 0.9
(2019/04/12)
Size update From 13.85 to 13.80
(2019/04/12)

Material		Plating/Finish	Remark
A	Insulating body	PA66 UL 94V-0	Green
B	Terminal	Brass	Tin
C	Screw	Steel	Zinc
D	Clamp	Brass	Nickel
E			



HOW DER
ELECTRONIC CO.,LTD

PART NAME
Terminal Blocks

UNIT
MM

REVISION

DESIGN	CHECK	APPROVED	DRAWING NO.
DATE	DATE	DATE	
2009/09/03			

CERTIFIED



SHEET
1/1

