| REVISIONS | | | | |
|---|---|---|---|---|
| ZONE | REV | DESCRIPTION | DATE | APPROVED |










| ✓ | Poles | A±0.30 | B±0.20 | | 17 | 131.14 | 121.92 |
|---|---|---|---|---|---|---|---|
| | 02 | 16.94 | 7.62 | | 18 | 138.86 | 129.54 |
| | 03 | 24.56 | 15.24 | ⇩ | Poles | A±0.45 | B±0.35 |
| | 04 | 32.18 | 22.86 | | 19 | 146.48 | 137.16 |
| | 05 | 39.80 | 30.48 | | 20 | 154.10 | 144.78 |
| | 06 | 47.42 | 38.10 | | 21 | 161.72 | 152.40 |
| ⇩ | Poles | A±0.35 | B±0.25 | | 22 | 169.34 | 160.02 |
| | 07 | 55.04 | 45.72 | | 23 | 176.96 | 167.64 |
| | 08 | 62.66 | 53.34 | | 24 | 184.58 | 175.26 |
| | 09 | 70.28 | 60.96 | ⇩ | Poles | A±0.50 | B±0.40 |
| | 10 | 77.90 | 68.58 | | 25 | 192.20 | 182.88 |
| | 11 | 85.52 | 76.20 | | 26 | 199.82 | 190.50 |
| | 12 | 93.14 | 83.82 | | 27 | 207.44 | 198.12 |
| ⇩ | Poles | A±0.40 | B±0.30 | | 28 | 215.06 | 205.74 |
| | 13 | 100.76 | 91.44 | | 29 | 222.68 | 213.36 |
| | 14 | 108.38 | 99.06 | | 30 | 230.30 | 220.98 |
| | 15 | 116.00 | 106.68 | | 31 | 237.92 | 228.60 |
| | 16 | 114.30 | 114.30 | | 32 | 236.22 | 236.22 |

Screws Torque: 12 In-Lb
Wire Range: 16~22 AWG
Rated: 15 Amperes.AC300V
Operation Temperature: -55°C~+105°C
Insulation withstands volt: AC2000V min
Insulation resistance: >1000MΩ DC500V

Part Number:

FTB-702-XXP

02~32 Poles

| | Material | | Plating/Finish | Remark |
|---|---|---|---|---|
| A | Insulating body | PA66 94V-0 | | Black |
| B | Terminals | Brass | Tin | |
| C | Screws | Steel | Nickel | |
| D | Cover | PC | | |
| E | | | | |

2 Size update From 9.55 to 9.5 (2017/07/15)

1 Size update From 1.1 to 1.0 (2017/07/15)

**HOW DER**
ELECTRONIC CO.,LTD

| PART NAME | UNIT | REVISION |
|---|---|---|
| Teminal Blocks | MM | |

| DESIGN | CHECK | APPROVED | DRAWING NO. | CERTIFIED | | SHEET |
|---|---|---|---|---|---|---|
| DATE 2009/09/03 | DATE | DATE | | | | 1/1 |

http://www.howder-tw.com
E-mail:info@howder-tw.com
Tel:886-2-2223-1026
Fax:886-2-2221-6471

ROHS