



✓ Poles	A±0.30	B±0.20	17	59.5	56.0
02	7.0	3.5	18	63.0	59.5
03	10.5	7.0	↓ Poles	A±0.45	B±0.35
04	14.0	10.5	19	66.5	63.0
05	17.5	14.0	20	70.0	66.5
06	21.0	17.5	21	73.5	70.0
↓ Poles	A±0.35	B±0.25	22	77.0	73.5
07	24.5	21.0	23	80.5	77.0
08	28.0	24.5	24	84.0	80.5
09	31.5	28.0	↓ Poles	A±0.50	B±0.40
10	35.0	31.5	25	87.5	84.0
11	38.5	35.0	26	91.0	87.5
12	42.0	38.5			
↓ Poles	A±0.40	B±0.30			
13	45.5	42.0			
14	49.0	45.5			
15	52.5	49.0			
16	56.0	52.5			

Screws Torque: 1 In-Lb
 Wire Range: 12~28 AWG
 Rated: 20 Amperes, AC300V
 Operation Temperature: -40°C~+105°C
 Insulation withstands volt: AC1600V min
 Insulation resistance: >2000MΩ DC500V

Part Number:

HD-351-XXP

02~26 Poles

Size update From 4.20 to 4.38 (2021/04/29)
 Size update From 7.50 to 7.50 (2018/10/17)

Material		Plating/Finish	Remark
A	Insulating body	PA66 UL 94V-0	Green
B	Terminal	Brass	Tin
C	Screw	Steel	Yellow Zinc
D	Cage Clamp	Brass	Tin
E			

		HOW DER ELECTRONIC CO., LTD		PART NAME Terminal Blocks		UNIT MM		REVISION SHEET 1/1	
DESIGN	CHECK	APPROVED	DRAWING NO.	CERTIFIED					
DATE	DATE	DATE							
2009/09/03									



http://www.howder-ek.com
 E-mail:info@howder-ek.com
 Tel:896-2-2223-1026
 Fax:896-2-2221-6471