

✓	Poles	A±0.30	B±0.20	17	158.55	148.5
02		34.8	24.75	18	166.8	156.75
03		43.05	33.00	↓	Poles	A±0.45 B±0.35
04		51.30	41.25	19	175.05	165.0
05		59.55	49.5	20	183.3	173.25
06		67.80	57.75	21	191.55	181.5
↓	Poles	A±0.35	B±0.25	22	199.8	189.75
07		76.05	66.00	23	208.05	198.0
08		84.30	74.25	24	216.3	206.25
09		92.55	82.50	↓	Poles	A±0.50 B±0.40
10		100.8	90.75	25	224.55	214.5
11		109.05	99.00	26	232.8	222.75
12		117.3	107.25	27	241.05	231.0
↓	Poles	A±0.40	B±0.30	28	249.3	239.25
13		125.55	115.5	29	257.55	247.5
14		134.28	123.75	30	265.8	255.75
15		142.05	132.0			
16		150.3	140.25			

Screws Torque: 12 In-Lb
Wire Range: 16~22 AWG
Rated: 20 Amperes,AC300V
Operation Temperature: -55°C~+95°C
Insulation withstands volt: AC2000V min
Insulation resistance: >1000MΩ DC500V

Part Number:
FTB-805-XXPH

02~30 Poles

- △4

Size update From 14.0 to 13.9
(2017/08/09)
- △3

Size update From 1.65 to 1.55
(2017/08/09)
- △2

Size update From 6.6 to 6.7
(2017/08/09)
- △1

Size update From 1.65 to 1.80
(2017/08/09)

DESIGN

CHECK

DATE

APPROVED

DATE

DRAWING NO.

CERTIFIED

1/1

HOW DER

ELECTRONIC CO.,LTD

PART NAME

Terminal Blocks

UNIT

MM

REVISION

Technical drawing of the FTB-805-XXPH terminal block. The top view shows a rectangular block with dimensions A (P+2)×8.25±1.8 and B (P+1)×8.25. It features four circular terminals with a diameter of Ø3.50±0.10. The side view shows the block's profile with dimensions 6.70±0.10, 1.55±0.10, 8.60±0.10, 8.25±0.08, and 1.00±0.10.

Technical drawing of the FTB-805-XXPH terminal block showing a cross-section view. It includes dimensions 15.60±0.10, 13.90±0.10, 1.00, 15.30±0.10, and 0.80. Labels A, B, C, and D indicate specific internal features.

http://www.howder-tw.com
E-mail:info@howder-tw.com
Tel:886-2-2223-1026
Fax:886-2-2221-6471